

Technical drawing of a bridge structure, showing plan and section views.

Plan View (Top):

- Overall length: 31.14m (31.14m x 0.15).
- Span lengths: 10.00m, 10.00m, 10.00m.
- Section A-A is indicated across the bridge.
- Material specifications: 2N10B10 C=100, 2N20B10 C=110, 3N14N30B C=15, 3N14N30B C=15.

Section View (Bottom):

- Section A-A shows the bridge cross-section.
- Overall width: 10.00m.
- Span lengths: 10.00m, 10.00m, 10.00m.
- Material specifications: 2N10B10 C=100, 2N20B10 C=110, 3N14N30B C=15, 3N14N30B C=15.

Legend:

- 2N10B10 C=100
- 2N20B10 C=110
- 3N14N30B C=15
- 3N14N30B C=15

[illegible]

Elemento	Pos.	Diam.	Q.	Esquema	Comp. (cm)	Total (cm)	CA-50 (kg)	CA-60 (kg)
V1	1	Ø10	2		1091	2182	13.4	
	2	Ø10	2		1109	2182	13.7	
	3	Ø5	63		84	5202		
				Total-10%			29.8	9.7
V2	1	Ø10	2		497	994	5.8	
	2	Ø10	2		498	996	6.0	
	3	Ø5	24		84	2104		
				Total-10%			13.0	3.5
V3	1	Ø10	2		301	604	4.0	
	2	Ø10	2		344	688	4.2	
	3	Ø5	17		84	1420		
				Total-10%			9.0	2.4
V4	1	Ø10	2		779	1558	9.6	
	2	Ø10	2		822	1644	10.1	
	3	Ø5	46		84	3654		6.7
				Total-10%			21.7	6.7
V5	1	Ø10	2		728	1456	9.0	
	2	Ø10	2		737	1474	9.1	
	3	Ø5	41		84	3444		5.4
				Total-10%			19.0	5.5
V6	1	Ø10	2		860	1680	10.4	
	2	Ø10	2		869	1700	10.7	
	3	Ø10	2		880	1760	11.3	
	4	Ø10	2		895	1916	11.8	
	5	Ø5	73		84	8132		9.6
				Total-10%			35.2	10.0
V7	1	Ø10	2		476	952	5.9	
	2	Ø10	2		494	988	6.1	
	3	Ø5	23		84	1932		
				Total-10%			13.2	3.2
V8	1	Ø10	2		915	1830	11.3	
	2	Ø10	2		1090	2160	13.3	
	3	Ø10	1		166	166	1.1	
	4	Ø10	2		895	1790	11.0	
	5	Ø10	2		1057	2134	13.2	
	6	Ø5	112		84	4008		14.8
				Total-10%			54.9	16.3
				Ø5:		0.0	0.7	
				Ø10:		196.7	6.0	
				Total:		196.7	6.7	

Elemento	Pos.	Diag.	Q.	Esquema (cm)	Comp. (cm)	Total (cm)	CA-50 (kg)	CA-60 (kg)
V1	1	Ø10	2		314	628	39	
	2	Ø10	2		332	664	41	
	3	Ø5	15		74	1110		1.7
					Total-10%		8.8	1.9
V2	1	Ø10	2		315	630	3.9	
	2	Ø10	2		338	716	4.4	
	3	Ø5	17		74	1256		2.0
					Total-10%		9.1	2.0
V3	1	Ø10	2		620	1840	11.4	
	2	Ø10	2		505	610	3.8	
	3	Ø10	2		240	480	3.0	
	4	Ø10	2		912	1824	11.2	
	5	Ø10	2		300	600	3.7	
	6	Ø5	30		74	2220		3.5
	7	Ø5	57		84	4768		7.5
					Total-10%		38.4	12.1
V4	1	Ø10	2		1115	2230	13.7	
	2	Ø10	2		590	1180	7.4	
	3	Ø10	1		225	225	1.3	
	4	Ø10	2		510	1020	6.3	
	5	Ø10	2		1069	2138	13.5	
	6	Ø10	2		573	1146	7.1	
	7	Ø5	34		74	2516		4.0
V5	1	Ø10	2		84	5502		8.3
	2	Ø10	2		84	5502		8.3
	3	Ø5	65		84	5502		8.3
					Total-10%		48.4	13.5
V5	1	Ø10	2		840	1680	15.4	
	2	Ø10	2		476	952	5.8	
	3	Ø10	2		638	1676	10.3	
	4	Ø10	2		458	916	5.6	
	5	Ø5	73		84	6132		9.6
					Total-10%		35.3	10.6
V6	1	Ø10	2		476	952	5.9	
	2	Ø10	2		494	988	6.1	
	3	Ø5	23		84	1932		3.0

[illegible]